

Spreader calibrations - Kuhn and Sulky **SUSTAIN**

Powered by **AGROTAIN**

The spreader settings below are for guidance only. The exact fertiliser rates and spreading patterns using these settings cannot be guaranteed as the application will be affected by the condition of the spreader itself and the environmental conditions at the time of application.

To ensure greater accuracy, the spreader should be recalibrated for application rate and spread pattern using a tray test. Up to date information can be found on the spreader manufacturers website.

Product Name	Spreader (Make/Model)	Spread Width (m)	Disc/Vane Type	Spreader Height	Tilt (°)	PTO /Disc speed (rpm)	Vane setting / Drop on point/ Discharge point	Application Rate (kg/Ha)	Forward speed (km/h)
SUSTAIN 46-0-0	Kuhn Axis 30.1	24	S4	50		540	6.5	200	12
SUSTAIN 46-0-0	Kuhn Axis 30.1	36	S8	50		540	9.5	200	12
SUSTAIN 38N 19S	Kuhn Axis 30.1	24	S4	50		540	6	250	10
SUSTAIN 38N 19S	Kuhn Axis 30.1	36	S8	50		540	8	250	10
SUSTAIN 33N 30S	Kuhn Axis 30.1	24	S4	50		540	6	250	10
SUSTAIN 33N 30S	Kuhn Axis 30.1	36	S8	50		540	8.5	250	10
SUSTAIN 38N 19S	Sulky X36	24	12/28	70		540	120	250	10
SUSTAIN 38N 19S	Sulky X36	24	24/36	70		540	117	250	10
SUSTAIN 38N 19S	Sulky X36	32	24/36	70		540	125	250	10
SUSTAIN 33N 30S	Sulky X36	24	12/28	70		540	120	250	10
SUSTAIN 33N 30S	Sulky X36	24	24/36	70		540	117	250	10
SUSTAIN 33N 30S	Sulky X36	32	24/36	70		540	125	250	10

Advanced nutrition for enhanced performance

t: 03333 239 230

e: productenquiry@originfertilisers.co.uk

www.originfertilisers.co.uk