

# Spreader calibrations - Vicon

The spreader settings below are for guidance only. The exact fertiliser rates and spreading patterns using these settings cannot be guaranteed as the application will be affected by the condition of the spreader itself and the environmental conditions at the time of application.

To ensure greater accuracy, the spreader should be recalibrated for application rate and spread pattern using a tray test. Up to date information can be found on the spreader manufacturers website.

Product Name	Spreader (Make/Model)	Spread Width (m)	Disc/Vane Type	Spreader Height	Tilt (o)	PTO /Disc speed (rpm)	Vane setting / Drop on point/ Discharge point	Application Rate (kg/Ha)	Forward speed (km/h)
SUSTAIN 46-0-0	Vicon RO XL	24	285mm	75		950 disc	I	200	12
SUSTAIN 46-0-0	Vicon RO XL	32	285mm	75	+8* Tilt	950 disc	D	200	12
SUSTAIN 38N 19S	Vicon RO XL	24	285mm	75		950 disc	K	250	10
SUSTAIN 38N 19S	Vicon RO XL	30	285mm	75		950 disc	H	250	10
SUSTAIN 33N 30S	Vicon RO XL	24	285mm	75		950 disc	L	250	10
SUSTAIN 33N 30S	Vicon RO XL	30	285mm	75		950 disc	H	250	10

Advanced nutrition for enhanced performance

t: 03333 239 230

e: [productenquiry@originfertilisers.co.uk](mailto:productenquiry@originfertilisers.co.uk)

[www.originfertilisers.co.uk](http://www.originfertilisers.co.uk)

# Spreader calibrations - ACCORD and TEAGLE **SUSTAIN** Powered by AGROTAIN™

The spreader settings below are for guidance only. The exact fertiliser rates and spreading patterns using these settings cannot be guaranteed as the application will be affected by the condition of the spreader itself and the environmental conditions at the time of application.

To ensure greater accuracy, the spreader should be recalibrated for application rate and spread pattern using a tray test. Up to date information can be found on the spreader manufacturers website.

Product Name	Spreader (Make/Model)	Spread Width (m)	Disc/Vane Type	Spreader Height	Tilt (o)	PTO /Disc speed (rpm)	Vane setting / Drop on point/ Discharge point	Application Rate (kg/Ha)	Forward speed (km/h)
SUSTAIN 38N 19S	Accord Exacta HL	24	285mm	75		950 disc	P	250	10
SUSTAIN 38N 19S	Accord Exacta HL	30	285mm	75		950 disc	M	250	10
SUSTAIN 38N 19S	Teagle Centreliner	24	268mm	85	+5* Tilt	540	N/A	250	10
SUSTAIN 38N 19S	Teagle Centreliner	28	268mm	100	+10* Tilt	540	N/A	250	10
SUSTAIN 33N 30S	Accord Exacta HL	24	285mm	75		950 disc	Q	250	10
SUSTAIN 33N 30S	Accord Exacta HL	30	285mm	75		950 disc	M	250	10
SUSTAIN 33N 30S	Teagle Centreliner	24	268mm	85	+5* Tilt	540	N/A	250	10
SUSTAIN 33N 30S	Teagle Centreliner	28	268mm	100	+10* Tilt	540	N/A	250	10

Advanced nutrition for enhanced performance

t: 03333 239 230

e: [productenquiry@originfertilisers.co.uk](mailto:productenquiry@originfertilisers.co.uk)

[www.originfertilisers.co.uk](http://www.originfertilisers.co.uk)